

# NEMA56C 90V&180V Standard TEFC

## Dimension Chart (All Dimensions in Inch.)

Model No.	D	2E	F	2F1	H	O	U	V	AB	AH	AJ	AK	BA	BB	BD	TAP	C
MD01AL	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
MD01BL	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
MD02AL	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
MD02BL	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
MD03AL	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	12.4
MD03BL	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	12.4
MD03AP	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
MD03BP	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
MD03AX	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	11.0
MD03BX	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	11.0
MD04AL	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	14.0
MD04BL	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	14.0
MD04AP	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	12.4
MD04BP	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	12.4
MD04AX	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
MD04BX	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	11.6
MD05AL	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	14.8
MD05BL	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	14.8
MD05AP	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	14.0
MD05BP	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	14.0
MD05AX	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	12.4
MD05BX	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	12.4
MD06AL	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	16.3
MD06BL	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	16.3
MD06AP	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	16.3
MD06BP	3.50	4.88	3.0	/	0.34Slot	5.63	0.625	1.88	4.13	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	16.3
MD07AL	3.50	4.88	3.0	/	0.34Slot	6.87	0.625	1.88	4.5	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	16.5
MD07BL	3.50	4.88	3.0	/	0.34Slot	6.87	0.625	1.88	4.5	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	16.5
MD07AP	3.50	4.88	3.0	/	0.34Slot	6.87	0.625	1.88	4.5	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	16.5
MD07BP	3.50	4.88	3.0	/	0.34Slot	6.87	0.625	1.88	4.5	2.06	5.875	4.5	2.75	0.12	6.5	3/8-16	16.5